


CAT5e U/UTP 24 AWG PVC

Ref. Std. ISO/IEC 11801 2nd ed., IEC 61156-5
EN 50173-1, EN 50288-3-1 ANSI EIA/TIA 568-D.2

72V



Application

They are used in cabling in offices, management, R&D buildings with high terminal density, signal communication in information communication systems.

IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T

IEEE 802.5 16 MB; ISDN; TPDDI; ATM

IEEE 802.3af (Type 1 PoE)

IEEE 802.3at (Type 2 PoE)

Construction

Conductor	Electrolytic solid copper conductor (Awg 24)
Insulation	Solid polyethylene (0,91±0,05mm)
Stranding	Cores are twisted in pairs, and all the pairs are twisted together
Outer sheath	PVC compound
Outer sheath color	RAL 7035 (other color on request)
Outer sheath diameter	4,90 ±0,30mm

Conductor resistance	Resistance imbalance	Capacitance	Capacity imbalance	Velocity of propagation	Signal delay	Characteristic impedance	Test voltage
max.95 Ω/km	max %1	nom. 50 pF/m	max. 1600 pF/km	66%	max.45 ns/100m	100 ± 5 Ω @100MHz	1000V

TCL	Segregation class	Bending radius	Temperature range	Insulation resistance	Operating voltage
min. level 2	b	fixed min. 4 x D flexing min. 8 x D	fixed -30°C ...+60°C flexing 0°C ...+50°C	min 5000 MΩ x m	72V

50 dB ≥
55 dB

Flame propagation
IEC 60332-1-2; VDE 0482-332-1-2; EN 60332-1-1

Frequency	Attenuation	Near end crosstalk (Next)	Ps-Next	Return Loss	ACR-N	ACR-F (ELFEXT)	PS-ACR-F (PS-ELFEXT)
MHz	dB/100	dB	dB	dB/100	dB/100	dB/100	dB/100
4	3,8	75	72	23	70	68	65
10	6	75	72	23	70	55	52
16	7,8	65	62	23	59	53	50
31,25	10,5	55	52	22	50	45	42
62,5	15,5	45	42	21	40	35	32
100	19	40	37	21	37	30	27
200	19	40	37	21	37	30	27