


Part Number: MRG1740



COAX RG174/U PVC

Product Description

COAX [0.5/1.52] RG174/U STRANDED PVC

Technical Specifications

Product Overview

Environmental Space:	Indoor - Euroclass Eca
Suitable Applications:	Coaxial communication cable based on MIL-C-17

Physical Characteristics (Overall)

Conductor

Stranding	Material	Construction n x D	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
Stranded	Copper clad steel	7x0.16 mm	0.48 mm	0.02 mm	1

Conductor Count:	1
Conductor Size:	26 AWG

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	Polyethylene	1.5 mm	0.15 mm

Outer Shield Material

Type	Material	Coverage [%]	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Braid	TC - Tinned Copper	85 %	1.97 mm	0.15 mm	4 %

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	2.8 mm	0.1 mm

OuterJacket1, Table Note:	According to European Standard HD 624
---------------------------	---------------------------------------

Electrical Characteristics

Conductor DCR

Max. Conductor DCR
317 Ohm/km

Capacitance

Nom. Capacitance	Capacitance Tolerance
100 pF/m	3 pF/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance
50 Ohm	2 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
-----------------	---------------------

10 MHz	11 dB/100m
200 MHz	42 dB/100m
1000 MHz	110 dB/100m

Delay

Nominal Velocity of Propagation (VP) [%]
66 %

Voltage

Voltage Rating [V]
1400 DC / 1000 V RMS

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-40°C To +70°C

Mechanical Characteristics

Max Recommended Pulling Tension:	90 N
----------------------------------	------

Standards

CPR Euroclass:	Eca
RG Type:	174/U Type
MIL Spec Rating:	MIL-C-17

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01
---------------------------------------	------------

Flammability, LS0H, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
-----------------------	---------------

Part Number

Variants

Item #	Color
MRG1740.0050	Black
MRG1740.00500	Black

History

Revision Number:	2
------------------	---

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.