



For more Information  
please call

1-800-Belden1



### General Description:

Industry Standard SMPTE 311M Cable, 4 power conductors, 2 SM fibers w/24 and 20 AWG stranded (7x32 and 19x32) TC conductors, PVC insulation, TC braid shield (95% coverage), PVC jacket.

### Usage (Overall)

**Suitable Applications:** SMPTE 311M Camera Cable

### Multi Conductor

#### Physical Characteristics

##### Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (mm)
2	24	7x32	TC - Tinned Copper	0.610
4	20	19x32	TC - Tinned Copper	0.940

##### Insulation

Insulation Material:

Insulation Material	Dia. (mm)	AWG
PVC - Polyvinyl Chloride	1.600	20
PVC - Polyvinyl Chloride	1.270	24

Insulation Color Code Chart:

Number	Color	Description
1	Red	24 AWG
2	Gray	24 AWG
3	White	20 AWG
4	Black	20 AWG
5	White/Black	20 AWG
6	Black/White	20 AWG

##### Individual Shield

#### Electrical Characteristics

Nom. Conductor DC Resistance:

Description	DCR @ 20°C (Ohm/km)
24 AWG	76.447
20 AWG	28.873

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
11.484

### Fiber

#### Physical Characteristics

**Fiber Type:** Single Mode/125/900 Micron

**Number of Fibers:** 2

**Mode Field Diameter @ 1310nm:** 9.5 +/-1 microns

**Clad Diameter:** 125 microns

**Core-clad Concentricity Error:** < to 1 micron

Primary Coating Material:	Acrylate
Buffer Tube Diameter:	900 microns
Buffer Tube Material:	PVC - Polyvinyl Chloride

**Buffer Tube Color Code Chart:**

Number	Color
1	Blue
2	Yellow

### Optical Characteristics

Maximum Attenuation @ 1310nm:	0.5 dB/km
Maximum Attenuation @ 1550nm:	0.5 dB/km

### Physical Characteristics (Overall)

#### Conductor

#### Outer Shield

**Outer Shield Material:**

Type	Outer Shield Material	Coverage (%)
Braid	TC - Tinned Copper	95.000

#### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Trade Name	Outer Jacket Material
Belflex®	PVC Blend - Polyvinyl Chloride Blend

#### Strength Member

Overall Strength Member Diameter:	.089
Strength Member Material:	302 Stainless Steel

#### Overall Cable

Overall Nominal Diameter:	9.195 mm
---------------------------	----------

### Mechanical Characteristics (Overall)

Operating Temperature Range:	-40°C To +75°C
Max. Recommended Pulling Tension:	2001.690 N
Min. Bend Radius/Minor Axis:	63.500 mm
Flex Cycle Rating:	UL1581, Sec. 1582: 15,000 Cycles @ 3.6
Crush Resistance:	Compression, FOTP-41: 397 lbs.
Impact Resistance:	FOTP-25: 20 Cycles @ 1.32 lbs.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
UL Rating:	CMR-OF
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## 7804R Composite - SMPTE 311M HDTV Cable

**Other Specification:** SMPTE 311

### Flame Test

**UL Flame Test:** UL1666 Vertical Shaft

**CSA Flame Test:** FT4

**IEEE Flame Test:** 1202

### Suitability

**Suitability - Indoor:** Yes

**Suitability - Outdoor:** Yes

**Suggested Connectors:** SMPTE 304M Connectors

### Plenum/Non-Plenum

**Plenum (Y/N):** No

**Plenum Number:** 7804P

### Electrical Characteristics (Overall)

**Other Electrical Characteristic 1:** Auxillary Conductors: DC Loop Resistance - 30 Ohms/km nom. (9.1 Ohms/1000ft.) Min. Insulation Resistance - 10, 000 Megohms x km Dielectric Strength - 1750 V RMS. Signal Conductors: DC Loop Resistance - 150 Ohms/km nom. (45.7 Ohms/1000 ft.) Insulation Resistance - 10, 000 Megohms/1000 ft. Dielectric Strength: 1750 V RMS

### Notes (Overall)

**Notes:** Bend Radius is based upon (FOTP-37) @ 20°C. Plenum version and other conductor counts/diameters available by special order.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
7804R B591000	1,000 FT	96.000 LB	BLACK, MATTE	C	COMPOSITE CAMERA CABLE
7804R B591640	1,640 FT	152.520 LB	BLACK, MATTE	C	COMPOSITE CAMERA CABLE
7804R B593280	3,280 FT	314.880 LB	BLACK, MATTE	C	COMPOSITE CAMERA CABLE
7804R B59500	500 FT	47.500 LB	BLACK, MATTE	C	COMPOSITE CAMERA CABLE

**Notes:**  
C = CRATE REEL PUT-UP.

Revision Number: 0    Revision Date: 09-13-2017

© 2019 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.