



**Part Number:** 1821R

Audio Snake Cable, #22-24pr, TC, Indiv. Shielded, CMR

## Product Description

Audio Snake Cable, Riser-CMR, 24-22 AWG tinned copper pairs, polyolefin insulation, individually shielded with Beldfoil® bonded to numbered/color-coded PVC jackets so both strip simultaneously, PVC jacket

## Product Specifications

### AG.Filter Attributes

Total Number of Conductors:	48
-----------------------------	----

## Technical Specifications

### AG\_0401

UL Flammability:	UL1666 Riser
CSA Flammability:	FT4

### APAC Standard

MII Order #39 (China RoHS):	Yes
-----------------------------	-----

### Applicable Patents

Patent:	<a href="http://www.belden.com/p">http://www.belden.com/p</a>
---------	---

### Bend Radius

Min Bend Radius/Minor Axis:	9.75 in
-----------------------------	---------

### CCB-Sub-Part Number

Plenum (Y/N):	No
---------------	----

## Contact Information

PHONE_NUM:	1-800-Belden1
------------	---------------

## EU Directive

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01

## North American Standard

CA Prop 65 (CJ for Wire & Cable):	Yes
CEC/C(UL) Specification:	CMG
NEC/(UL) Specification:	CMR

## Unused Attributes

Notes:	Pair jackets and shields are bonded so both strip simultaneously with automatic stripping equipment. Beldfoil« provides high reliability with ease of termination.
--------	--

## Use

Max Recommended Pulling Tension:	679 lbs
----------------------------------	---------

### Impedance:

Nominal Characteristic Impedance
50 Ohm

### Inductance:

Nominal Inductance
0.18 $\mu$ H/ft

### Conductor DCR:

Individual Pair Nominal Shield DCR	Nominal Conductor DCR	Nominal Outer Shield DCR
14.1 Ohm/1000ft	14.8 Ohm/1000ft	11.8 Ohm/1000ft

### Color Chart 1:

Number	Color
1	Brown

2	Red
3	Orange
4	Yellow
5	Green
6	Blue
7	Purple
8	Gray
9	White
10	Black
11	Tan
12	Pink
13	Gray/Brown Stripe
14	Gray/Red Stripe
15	Gray/Orange Stripe
16	Gray/Yellow Stripe
17	Gray/Green Stripe
18	Gray/Blue Stripe
19	Gray/Purple Stripe
20	Gray/Gray Stripe
21	Gray/White Stripe
22	Gray/Black Stripe
23	Gray/Tan Stripe
24	Gray/Pink Stripe
	Red and Black

## Delay:

Nominal Velocity of Propagation (VP) [%]

66 %

## Voltage:

UL Voltage Rating

300V RMS V

### Current:

Max. Recommended Current [A]

1.45 Amps per conductor @ 25°C

### Innershield:

Type	Material	Material Trade Name	Coverage [%]	Drainwire AWG	Drainwire Construction n x D	
Tape	Aluminum Foil-Polyester Tape			Beldfoil®	100 %	22 7x30 mm
		TC - Tinned Copper				

### Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
31 pF/ft	56 pF/ft

### Innerjacket:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.133 in

### Insulation:

Material	Nominal Diameter
PO - Polyolefin	0.05 in

### Outerjacket 1:

Material	Nominal Diameter	Ripcord
PVC - Polyvinyl Chloride	0.969 in	Yes

### Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
22	7x30	TC - Tinned Copper	0.03 in	24

### Outershield 1:

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D	
Tape	Aluminum Foil-Polyester Tape			Beldfoil®	100 %	TC - Tinned Copper	18 19x30 mm

# Product Variants

Part Number	Color	Put-Up Type	Length
1821R	BLACK	Reel	1000 ft
1821R	BLACK	Reel	305 m
1821R 0101000	BLACK	Reel	1000 ft
1821R	BLACK	Reel	500 ft
1821R	BLACK	Reel	152 m
1821R 010500	BLACK	Reel	500 ft
1821R	BLACK	Reel	500 m
1821R			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.