


CAT6A S/FTP 625 MHZ 23 AWG LSOH

72 V

ISO/IEC 11801-1 ed.1.0(Class F), IEC 61156-5
EN 50173-1,EN 50288-2-1, ANSI /TIA 568.2-D



Application

They are used in cabling in offices, management, R&D buildings with high terminal density, signal communication in information communication systems.

10 Base-T (IEEE 802.3)
100 Base-T (IEEE 802.3u)
1000Base-T (IEEE 802.3u)
10G Base-T Gigabit Ethernet
IEEE 802.3af (Type 1 PoE)
IEEE 802.3at (Type 2 PoE)
IEEE 802.3bt (Type 3 PoE)
IEEE 802.3bt (Type 4 PoE)
ATM 155
Token ring (IEEE 805.5)
TP-PMD (ANSI X3T9.5)
Power over HDBaseT (PoH)

Construction

Conductor	Electrolytic solid copper conductor (Awg 23)
Insulation	Foam/skin polyethylene compound(1,32±0,05mm)
Screen	Aluminium/pet tape
Stranding	Screened 4 pairs of common twist
Screen	Tinned copper drain wire; Tinned copper braid (%30 cov.)
Outer sheath	HFFR compound
Outer sheath color	RAL 4001 (other color on request)
Outer sheath diameter	7,10 ±0,30mm
Ripcord	Yes

Conductor resistance	Resistance imbalance	Capacitance	Capacity imbalance	Velocity of propagation	Signal delay	Characteristic impedance	Test voltage
max.75 Ω/km	max %1	nom. 43 pF/m	max. 1600 pF/km	78%	max.45 ns/100m	100 ± 5 Ω @100MHz	1000V

Transfer Impedance	TCL	Coupling attenuation	Segregation class	Bending radius	Temperature range	Insulation resistance	Operating voltage
Grade 1	min. level 2	Type I	d	fixed min. 4 x D flexing min. 8 x D	fixed -30°C ...+60°C flexing 0°C ...+50°C	min 5000 MΩ x m	72V
at 1/10/30/100 Mhz	50 dB ≥	30 to 100 Mhz					
10<10<15<40 mΩ/m	55 dB	> 85					

Flame propagation	Smoke density	Corrosive gases	Halogen free
IEC 60332-3-24; IEC 60332-1-2; VDE 0482-332-1-2; EN 60332-1-1	IEC 61034-2 VDE 0482-1034-2 EN 61034-2	IEC 60754-2 VDE 0482-267-2-3 EN 60754-2	IEC 60754-1 VDE 0482-267-2-1 EN 60754-1

Frequency	Attenuation	Near end crosstalk (Next)	Ps-Next	Return Loss	ACR-N	ACR-F (ELFEXT)	PS-ACR-F (PS-ELFEXT)	PSANEXT (Alien CrossTalk)	PSAAACRF (Alien CrossTalk)
MHz	dB/100	dB	dB	dB/100	dB/100	dB/100	dB/100	dB	dB
4	3,6	90	80	23	70	90	90	95	95
10	5,6	95	90	26	60	85	90	95	95
16	7,1	95	90	28	55	95	90	95	95
31,25	10,5	90	85	25	46	85	85	95	85
62,5	14,6	90	90	25	37	80	80	95	80
100	18,3	90	90	23	29	75	70	95	75
250	29,5	90	75	20	10	70	65	95	75
400	36	75	75	23	-20	55	65	95	65
500	42	75	75	23	-23	55	55	95	60
600	46	85	75	23	-25	55	50	95	60
650	46	85	75	23	-25	55	50	95	60