

Speaker Cable Meridian Install SP260 CPR-Version; 2 x 6,00 mm²; FRNC Ø 11,20 mm; black; Cca

Art. No.: 460-0051FC



General Data

Article number :	460-0051FC
Name :	Meridian Install SP260 CPR-Version
EAN :	4049371435970
Properties :	Analog
Properties :	Halogen-free / LSZH
Properties :	FRNC flame retardant
Properties :	OFC oxygen free copper
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 100 V
Application :	Speaker Cable
Application :	Installation cable
Colour :	black
BPVo-Euroclass :	Cca

Technical Data

Construction :	(2LIY6,0mm ²)Y
Jacket material :	FRNC
Jacket Ø [mm] :	11.20
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	6,00
Inner conductor Ø (audio) [mm] :	2,76
AWG (audio) :	10
Copper strands (audio) :	84
Copper strand Ø (audio) [mm] :	0,30
Conductor insulation Ø [mm] :	4,70
Weight per 1 m [g] :	226
Fire load per m [kWh] :	0,81
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-30
Temperature max. [°C] :	70
Width [mm] :	11,4
[mm] :	11,2

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	125
Insulation resist. per 1 km [GΩ] :	0,005
Insulation resist. per 1 km (audio) [GΩ] :	0,005
Conductor resistance per 1 km [Ω] :	3,3