



Product: [4855ELW](#)

4K UHD Coax for 12G-SDI, 75 Ohm, Mini RG-59, 21.5 AWG Solid SC, Foil + 95% TC Braid, LSZH Jkt

Product Description

75 Ohm SDI Coax, Mini RG-59, 21.5 AWG Solid Silvered Copper Conductor, PE Insulation, Foil + 95% Tinned Copper Braid Shield, LSZH Jacket

Technical Specifications

Product Overview

Suitable Applications:	Ultra-High Definition Digital Video, 4K Single-link 12 Gb/s UHDTV, 4K D-Cinema, 8K Quad-link UHDTV, HD-SDI 1080p
------------------------	--

Construction Details

RG Type:	Mini 59
----------	---------

Conductor

Size	Stranding	Nom. Diameter	Material
21.5 AWG	Solid	0.026 in	SC - Silvered Copper

Insulation

Material	Nom. Insulation Diameter
PE - Polyethylene (Foam)	0.114 in (2.90 mm)

Outer Shield

Layer	Outer Shield Type	Material	Material Trade Name	Coverage
1	Tape	Tri-Laminate (Alum+Poly+Alum)	Duofoil®	100%
2	Braid	Tinned Copper (TC)		95%

Outer Jacket

Material	Nom. Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant)	0.176 in (4.47 mm)

Electrical Characteristics

Return Loss (RL)

Frequency	Min. Return Loss
5 - 1600 MHz	23 dB
1600 - 4500 MHz	21 dB
4500 - 12000 MHz	15 dB

Attenuation

Frequency	Nom. Attenuation
1 MHz	0.34 dB/100ft
3.58 MHz	0.58 dB/100ft
5 MHz	0.67 dB/100ft
6 MHz	0.75 dB/100ft
7 MHz	0.79 dB/100ft
10 MHz	0.94 dB/100ft
12 MHz	1.04 dB/100ft
25 MHz	1.45 dB/100ft
55 MHz	2.15 dB/100ft

67.5 MHz	2.40 dB/100ft
71.5 MHz	2.46 dB/100ft
88.5 MHz	2.74 dB/100ft
100 MHz	2.92 dB/100ft
135 MHz	3.39 dB/100ft
143 MHz	3.49 dB/100ft
180 MHz	3.91 dB/100ft
270 MHz	4.81 dB/100ft
360 MHz	5.55 dB/100ft
540 MHz	6.81 dB/100ft
720 MHz	7.87 dB/100ft
750 MHz	8.04 dB/100ft
1000 MHz	9.30 dB/100ft
1500 MHz	11.45 dB/100ft
2000 MHz	13.29 dB/100ft
2250 MHz	14.13 dB/100ft
3000 MHz	16.47 dB/100ft
4500 MHz	20.56 dB/100ft
6000 MHz	24.05 dB/100ft
12000 MHz	35.38 dB/100ft

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
18.5 Ohm/1000ft	3.8 Ohm/1000ft (12 Ohm/km)	16.3 pF/ft (53.5 pF/m)	75 Ohm	82%

Voltage

Voltage Rating
300 V (RMS)

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	-30°C to +75°C

Bend Radius

Installation Min.
1.7 in

Max. Pull Tension:	40 lbs (18 kg)
Bulk Cable Weight:	17 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Euroclass Cca, Indoor, Aerial - Black only, When supported by messenger wire
CPR Compliance:	CPR Euroclass: Cca-s1,d1,a1
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.41 Revision Date: 04-08-2022
----------------------	---

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.