

BREAKOUT CABLE SJNMA HFFR

IT-V(ZN)H
IEC 60754-1, IEC 60794-1-21, IEC 60793-1-2, IEC 60794-3-12
Optical Fiber, Strength Member, LSZH/HFFR Sheath



KEY FEATURES	Cable Design
• Easy to Strip • Direct Termination • Small Diameter • Complete Dry Design • Halogen Free Fire Retardant / Low Smoke ZerHalogen • Flexible • Low Installation Cost • Non Metallic Desing	1. Optical Fiber 2. 900 mic. Tight 3. Aramid Yarn 4. Ripcord 5. LSZH/HFFR Sheath

PHYSICAL DESCRIPTION		
Fiber Type	SM G657 A1	
Fiber Colors	Blue	
Strength Elements	Water Blocking Aramid Yarns	
Outer Jacket	Yellow- LSZH/HFFR Sheath	
MECHANICAL AND ENVIRONMENTAL PROPERTIES		
Physical tests	Value	Standard
ShortTerm Tensile Strength	600N	IEC 60794-1-2 E1
Bend Radius	20 x cable diameter	IEC 60794-1-2 E11
Temperature Range	-20 to +60 °C	IEC 60794-1-2 F1

SHIPPING INFORMATION	PACKING INFORMATION
2000 mt ±%5	Plastic Reel or Plywood Reel

Number of Fibers	Tight Çapı (Nominal)	Zipcord Çapı (Nominal)	Outer Diameter (Nominal)	Approx. Weight (kg/km)
2	0.9	2.1	5.3±0.5	32

COLOR OF SUB UNITS / TIA-598											
1	2	3	4	5	6	7	8	9	10	11	12
											
Blue	Orange	Green	Brown	Slate	White	Red	Black	Yellow	Violet	Rose	Aqua

* For More Than 12 Tube With Black/White Tracer