

Part Number: 70006NH

DataTuff® PROFINET Cat 5e Type A - Permanent Installation Cable



Request Sample

Product Description

DataTuff PROFINET Type A, Cat 5e, 100Mb/s, Quad, AWG 22(1), Solid, Foil+ 85% Braid, No Halogen Jacket, UL AWG 21286

Technical Specifications

Product Overview

Environmental Space:	Indoor - Euroclass Eca
----------------------	------------------------

Physical Characteristics (Overall)

Conductor				
AWG	Stranding	Material	Nominal Diameter	No. of Conductors
22	Solid	BC - Bare Copper	0.65 mm	4
Conductor Count:				4
Total Number of Pairs:				1 Quad (2)
Conductor Size:				22 AWG

Insulation		
Material	Nominal Diameter	Diameter +/- Tolerance
Polyethylene	1.5 mm	0.05 mm
Bonded-Pair:		No

Color Chart	
Number	Color
Quad 1	White & Blue & Yellow & Orange

Inner Jacket Material	
Material	Nominal Diameter
FRNC / LSZH Bedding	3.9 mm

Outer Shield Material			
Type	Material	Thickness of Foil	Min. Coverage [%]
Tape	Aluminum/Polyester	50 µm	
Braid	TC - Tinned Copper		85 %

Outer Jacket Material			
Material	Color	Nominal Diameter	Diameter +/- Tolerance
LSZH / FRNC (UV stabilised and oil resistant)	Green (RAL 6018)	6.5 mm	0.2 mm

Construction and Dimensions

Cabling	
Description	
1 quad with center filler	

Electrical Characteristics

Conductor DCR

Max. Conductor DCR
57.1 Ohm/km

Impedance

Frequency [MHz]	Nominal Characteristic Impedance	Nominal Characteristic Tolerance
1 - 100	100 Ohm	15 Ohm

Delay

Max. Delay	Nominal Velocity of Propagation (VP) [%]
530 ns/100m	68 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. ACRF (ELFEXT) [dB]	Min. SRL (Structural Return Loss)
1 MHz	2.1 dB/100m	65.3 dB	64 dB	
4 MHz	4.1 dB/100m	56.3 dB	52 dB	23 dB
10 MHz	6.5 dB/100m	50.3 dB	44 dB	25 dB
16 MHz	8.3 dB/100m	47.2 dB	40 dB	25 dB
31.25 MHz	11.7 dB/100m	42.9 dB	34 dB	23.6 dB
62.5 MHz	17 dB/100m	38.4 dB	28 dB	21.5 dB
100 MHz	22 dB/100m	35.3 dB	24 dB	20.1 dB

Transfer Impedance

Frequency [MHz]	Transfer Impedance
10 Mhz	Max. 10 mOhm/m

Voltage

Voltage Rating [V]
300 V

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-40°C to +70°C
Operating Temp Range:	-40°C To +70°C

Mechanical Characteristics

Oil Resistance:	IEC 60811-2-1
-----------------	---------------

Standards

ISO/IEC Compliance:	ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011
CPR Euroclass:	Eca
Data Category:	Category 5e

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2014-10-21
---------------------------------------	------------

Flammability, LS0H, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
Amount of Halogen acc. to IEC 60754-1 & EN50267-1:	Zero

Part Number

Variants

Item #	Color
70006NH.011000	Green
70006NH.01305	Green
70006NH.01500	Green
70006NH.01B100	Green

Patent:	https://www.belden.com/resources/patents
---------	---

History

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.