

NBB75DSGB

Grounded BNC chassis connector, solder version in black D-shape housing

Neutrik's BNC chassis connectors offer a true 75 Ω design for serial and digital (HD) signals. The machined brass connector body provides an extremely rugged and non-abrasive connection over long term use and is in addition recessed and therefore well protected in a D-shape housing (audio industry standard).



Features & Benefits

- Gold plated center contact
- True 75 Ω design meets the stringent HD requirements
- Grounded panel mount
- Standard D-shape housing - provides flush mounting and protection from damage
- Color coding possible

Technical Information hide

Product	
Title	NBB75DSGB
Connection Type	BNC 75 Ω
Gender	female
Electrical	
Signal Type	HD, SDI, Video, AES/EBU, Composit, YUV, RGB, RGBH, RGBHV
Contact resistance	≤ 3 m Ω (inner)
Contact resistance	≤ 2 m Ω (outer)
Dielectric strength	1,5 kVdc
Impedance	75 Ω
Insulation resistance	> 5 G Ω
Rated voltage	<50 V
VSWR	≤ 1.03 / >37 dB up to 1 GHz ≤ 1.05 / >32 dB up to 2 GHz ≤ 1.08 / >28 dB up to 3 Ghz
Mechanical	
Insertion force	< 25 N
Lifetime	> 1000 mating cycles
Locking device	Bayonett
Mounting direction	Front mounting
Chassis shape	D
Material	
Contacts	Brass (CuZn39Pb3). 0.2 μ m AuCo (Center contact)
Home	Products About us Contact Support

Insert	PTFE
Shell	Polyacetal (POM) (Insulation Shell)
Shell plating	Optalloy®
D-Shape housing	Zinc diecast (ZnAl4Cu1) gal black chrome plating
Environmental	
Temperature range	-30 °C to +85 °C

Accessories

DSS-*



MFD



SCDP-*



SCDX



SCF



SCCD-W



SCD-W