

NC10MD-LX-B

10 pole male D-size receptacle, black chrome metal housing, duplex ground contact

Easy to assemble 10 pole XLR connectors with secure locking and proven Neutrik chuck type strain relief.



Features & Benefits

- Suitable for data offering CAT 5e performance and power up to 16 A and 50 V - exceeds PoE+ capabilities
- Superior ruggedness compared to RJ45 type connectors
- All metal housing offers best overall RF protection and electromagnetic shielding
- D-size housing provides installation compatibility with industry standard D mounting dimensions
- Receptacle with duplex ground contact for excellent signal integrity

Image gallery



Technical Information hide

Product	
Title	NC10MD-LX-B
Type	Chassis
Connection Type	XLR
Gender	male
Electrical	
Contact resistance	≤ 3 mΩ
Dielectric strength	1 kVdc (initial), 0.1 GΩ (after damp heat test)
Insulation resistance	> 10 GΩ
Number of electronical contacts	8 + 2
Rated current per contact	16 A (power pins), 3 A (data pins)
Transmission performance	CAT 5e
Mechanical	
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	2.5 mm² / AWG 14 (power pins), 1 mm² / AWG 18 (data pins)
Material	
Contact plating	0.2 µm Au hard alloy over 2 µm Ni
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Steel Ck67
Shell	Zinc diecast (ZnAl4Cu1)

Shell plating	Black chromium
Environmental	
Flammability	UL 94 HB
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C
Manufacturing Standard	IEC 61076-2-103

Accessories

CAS-DUMMY	DBA-BL	DSS-*	MFD
			
NDM	SCDM	SCDP-*	SCDR
			
SCDX	SCM	SCCD-W	
			