



Part Number: 82241

Analog Video, RG59, #23 Solid BCCS, 95% BC Braid, Flamarrest® Jacket, CMP

Product Description

23 AWG Solid .023" bare copper-covered steel conductor, plenum, FEP insulation, bare copper braid shield (95% coverage), Flamarrest® jacket.

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material		Nominal Diameter	No. of Coax
23	Solid	BCCS - Bare Copper Covered Steel		0.023 in	1
Total Num	ber of Conductors:		1		

Insulation:

Material	Nominal Diameter
FEP - Fluorinated Ethylene Propylene	0.134 in

Outershield 1:

Туре	Material	Coverage [%]
Braid	BC - Bare Copper	95 %

Outerjacket 1:

Material	Material Trade Name	Nominal Diameter
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.19 in

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR	Nominal Outer Shield DCR
49 Ohm/1000ft	2.6 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Shield	
19.5 pF/ft	

Impedance:

Nominal Characteristic Impedance	
75 Ohm	

High Frequency (Nominal/Typical):

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.5 dB/100ft
10 MHz	1 dB/100ft
50 MHz	2.3 dB/100ft
100 MHz	3.3 dB/100ft
200 MHz	5.2 dB/100ft
400 MHz	8.4 dB/100ft
700 MHz	11.6 dB/100ft
900 MHz	13.8 dB/100ft
1000 MHz	14.8 dB/100ft

Delay:

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.45 ns/ft	69.5 %

Inductance:

Nominal Inductance	
0.126 µH/ft	

Voltage:

Non-UL Voltage Rating	UL Voltage Rating
1700V RMS	300V RMS V

Use

Suitability - Indoor:	Yes
Max Recommended Pulling Tension:	62 lbs

Safety

UL Flammability:	NFPA 262

Temperature Range

Non-UL Temp Rating:	75°C °C
Operating Temp Range:	-20°C To +75°C °C
UL Temp Rating:	℃°C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	2 in

Part Number

Plenum (Y/N):	Yes
Non-Plenum Number:	8241

Standards

CA Prop 65 (CJ for Wire & Cable):	Yes
CEC/C(UL) Specification:	CMP
MII Order #39 (China RoHS):	Yes
NEC/(UL) Specification:	CMP
RG Type:	59/U
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No

Product Variants

Part Number	Color	Put-Up Type	Length
82241	NATURAL	Reel	1000 ft
82241	NATURAL	Reel	305 m
82241 8771000	NATURAL	Reel	1000 ft
82241	NATURAL	UnReel	1000 ft
82241 877U1000	NATURAL	UnReel	1000 ft
82241	NATURAL	UnReel	500 ft
82241	NATURAL	UnReel	152 m
82241 877U500	NATURAL	UnReel	500 ft
82241			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications described herein are subject to error or omission and to change without notice, and

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product tiself or the one that it becomes a part of. This Product Disclosure is of belden?s warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Part # 82241 | Page 4 of 4 | May 25, 2017

Belden Inc. | http://belden.catalog.belden.com/en/Products/Detail/PF_82241