

GABREAL GAT 4x4,0 FRNC-C

Construction

Conductor	Plain bare copper, stranding to class5 (EN 60228), 4,0 mm ² (50/0,30)
Insulation	Halogen Free (HF), Ø4,20 ± 0,05 mm
Core identifications	Blue, Red, Yellow, Green
Primary lay-up	Conductors stranded together
Outer sheath	HFFR compaund (Flex) (Pressure type)
Outer sheath color	Black

Marking

GABREAL GAT 440 PRoFLEX 4x4,0 TWINAX FRNC-C SPEAKER CABLE LOT CE 0001 m

Technical data

Conductor DC resistance	max. 4,95 Ω/km
Working temperature	Fixed -30 °C to +70 °C Flexible -5 °C to +70 °C
Bending radius	Moved: 15 x D Fixed: 7,5 x D

Properties

Flame retardant acc. to IEC 60332-1, 60332-3-24
Halogen free acc. to IEC 60754-1
Smoke density acc. to IEC 61034

Technical and dimension table

No of cores and cross section	Copper weight	Cable weight	Cable Diameter	Insulation resistance
N x mm ²	Nom. (kg/km)	Nom. (kg/km)	Nom. ± %10 (mm)	Min. (MΩ x km)
4 x 4,0	130	290	12,50	200