

NF-Phono cable SC-Aquila Control; 4 x 0,14 mm²; 2 x 0,14 mm²; PVC; blue

Art. No.: 800-0152

ANALOG

OFC



General Data

Article number :	800-0152
Name :	SC-Aquila Control
EAN :	4049371003230
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Studio / Broadcast
Application :	NF-Phono cable
Colour :	blue
BPVo-Euroclass :	Fca

Conductor resistance per 1 km [Ω] :

149

Technical Data

Signal transmission :	asymmetrical
Jacket material :	PVC
Number of Channels (audio) :	1
Number of Channels (control) :	2
Inner conductor (audio) :	4
Inner conductor (audio) [mm ²] :	0,14
Inner conductors (control) [mm ²] :	0,14
AWG (audio) :	26
AWG (control) :	26
Shielding :	Copper braiding + Polyester foil
Copper strands (audio) :	18
Copper strands (control) :	18
Copper strand Ø (audio) [mm] :	0,10
Copper strand Ø (control) [mm] :	0,10
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	2,20
Weight per 1 m [g] :	124
Fire load per m [kWh] :	0,44
Style variant :	twin
Packing :	50m spool
Temperature min. [°C] :	-20
Temperature max. [°C] :	70
Width [mm] :	21
[mm] :	4,5

Electrical Data

Capac. cond./shield. per 1 m (audio) [pF] :	60
Capacity wire/electic screen at 1m (control) [pF] :	60
Insulation resist. per 1 km [GΩ] :	0,01
Insulation resist. per 1 km (audio) [GΩ] :	0,01
Insulation resist. per 1 km (control) [GΩ] :	0,01