



Part Number: 8410

Microphone Cable, #25-1c, TC, O/A Braid, CM

Product Description

25 AWG stranded (7x33) composite copper conductor, EPDM rubber insulation, rayon braid + TC braid shield (80% coverage), cotton serve, cotton serve, EPDM rubber jacket.

Product Specifications

AG.Filter Attributes

Total Number of Conductors:	1
-----------------------------	---

Technical Specifications

APAC Standard

MII Order #39 (China RoHS):	Yes
-----------------------------	-----

Applicable Patents

Patent:	http://www.belden.com/p
---------	---

Bend Radius

Min Bend Radius/Minor Axis:	2.5 in
-----------------------------	--------

CCB-Sub-Part Number

Plenum (Y/N):	No
---------------	----

Contact Information

PHONE_NUM:	1-800-Belden1
------------	---------------

EU Directive

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01

North American Standard

CA Prop 65 (CJ for Wire & Cable):	Yes
-----------------------------------	-----

Use

Max Recommended Pulling Tension:	60 lbs
----------------------------------	--------

Impedance:

Nominal Characteristic Impedance

52 Ohm

Conductor DCR:

Nominal Conductor DCR

Nominal Outer Shield DCR

45.1 Ohm/1000ft	5.8 Ohm/1000ft
-----------------	----------------

Voltage:

Non-UL Voltage Rating

3000V DC

Current:

Max. Recommended Current [A]

1.9 Amps per conductor @25°C

Capacitance:

Nom. Capacitance Conductor to Shield

33 pF/ft

Insulation:

Material

Nominal Diameter

Nominal Wall Thickness

EPDM - Ethylene Propylene Diene Monomer Rubber	0.154 in	0.058 in
--	----------	----------

Outerjacket 1:

Material

Nominal Diameter

Nominal Wall Thickness

Separator Material

EPDM - Ethylene Propylene Diene Monomer Rubber	0.245 in	0.024 in	Cotton Serve
--	----------	----------	--------------

Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Coax
25	3x33	High Conductivity TC - Tinned Copper	0.021 in	1

Outershield 1:

Type	Layer	Material	Coverage [%]
Braid		1 Cotton	
Braid	2	TC - Tinned Copper	80 %
Rayon Braid in			

Product Variants

Part Number	Color	Put-Up Type	Length
8410	BLACK	Reel	500 ft
8410	BLACK	Reel	152 m
8410 010500	BLACK	Reel	500 ft
8410			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.