



**Part Number:** 1521A

RGB Video, Mini #30-4 Coax Stranded TC, CL2

## Product Description

RGB Video Coax, CL2-Rated, 4-30 AWG stranded tinned copper conductors, foam HDPE insulation, Duofoil® +90% tinned copper braid shield, overall Beldfoil® shield, inner PVC jackets, PVC jacket

## Technical Specifications

### Construction and Dimensions

#### Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Coax
30	7x38	TC - Tinned Copper	0.012 in	4
Total Number of Conductors:			4	

#### Insulation:

Material	Nominal Diameter
FHDPE - Foam High Density Polyethylene	0.056 in

#### Color Chart 3:

Number	Color
1	Red
2	Green
3	Blue
4	White

#### Innershield:

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Aluminum Foil-Polyester Tape-Aluminum Foil	Duofoil®	100 %
Braid	2	TC - Tinned Copper		90 %

#### Innerjacket:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.102 in

#### Outershield 1:

Type	Material	Material Trade Name	Coverage [%]
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %

#### Outerjacket 1:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.31 in

## Electrical Characteristics

#### Conductor DCR:

Nominal Conductor DCR	Nominal Outer Shield DCR
100 Ohm/1000ft	9.5 Ohm/1000ft

#### Capacitance:

Nom. Capacitance Conductor to Other Conductor to Shield
17.3 pF/ft

Sweep Testing:	100% sweep tested. 10MHz to 40MHz.
----------------	------------------------------------

#### Impedance:

Nominal Characteristic Impedance
75 Ohm

#### High Frequency (Nominal/Typical):

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.8 dB/100ft
5 MHz	1.5 dB/100ft
10 MHz	2.2 dB/100ft
30 MHz	4 dB/100ft
50 MHz	5.4 dB/100ft
100 MHz	8.2 dB/100ft
200 MHz	12.5 dB/100ft
400 MHz	18.9 dB/100ft
700 MHz	26.5 dB/100ft
900 MHz	30.8 dB/100ft
1000 MHz	32.8 dB/100ft

## Delay:

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.3 ns/ft	78 %

## High Freq:

Min. RL (Return Loss) [dB]
25 dB

## Voltage:

UL Voltage Rating
30V RMS (UL AWM Style 1354) V
300V RMS (CL2)

## Use

Max Recommended Pulling Tension:	56 lbs
----------------------------------	--------

## Temperature Range

Non-UL Temp Rating:	60°C °C
Operating Temp Range:	-40°C To +60°C °C
UL Temp Rating:	60°C (UL AWM Style 1354) °C

## Mechanical Characteristics

Min Bend Radius/Minor Axis:	3 in
-----------------------------	------

## Part Number

Plenum (Y/N):	No
Suggested Connectors:	Kings#2025-57-9

## Standards

CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
NEC/(UL) Specification:	CL2
RG Type:	Mini
UL AWM Style:	UL Style 1354 (each coax); UL Style 2688 (overall)
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No

## Product Variants

Part Number	Color	Put-Up Type	Length
1521A	BLACK	Reel	1000 ft
1521A	BLACK	Reel	305 m
1521A 0101000	BLACK	Reel	1000 ft
1521A	BLACK	Reel	500 ft
1521A	BLACK	Reel	152 m
1521A 010500	BLACK	Reel	500 ft
1521A			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.