



RT4MP

4 pole TINY xlr male chassis connector, nickel housing, gold plated contacts, max. panel thickness: 6 mm

- Front mountable design
- Shielded system – high noise immunity and EMI protection
- Watertight chassis connector, even in unmated condition



Technical Information [hide](#)

| | |
|---------------------------|---------------------------|
| Product | |
| Title | RT4MP |
| Electrical | |
| Contact resistance | < 10 mΩ |
| Dielectric strength | > 0.5 kVdc |
| Insulation resistance | > 1 GΩ |
| Rated current per contact | < 5 A |
| Mechanical | |
| Lifetime | > 5000 mating cycles |
| Panel thickness | max. 6 mm |
| Wiresize | 0.22 mm² |
| Wiresize | 24 AWG |
| Material | |
| Contact plating | Au |
| Contacts | Brass (CuZn38Pb3) |
| Insert | PA 6.6 30 % GF |
| Shell | ZuAl4Cu1 |
| Shell plating | Nickel |
| Environmental | |
| Solderability | Complies with IEC 68-2-20 |
| Temperature range | -30 °C to +85 °C |

Data subject to change without prior notice. © 2012 NEUTRIK AG ® ALL RIGHTS RESERVED

REAN[®]
REAN a brand of Neutrik AG