

NLT4MP-BAG

4 pole male chassis connector, black-chrome metal housing, solder or ¼" flat tabs

The speakON STX Series was especially designed for heavy duty amplifier-loudspeaker applications like professional touring. The extremely rugged and durable STX Series features an all metal housing.



Features & Benefits

- Extremely robust metal housing designed for harsh and demanding environment
- Ideal product for touring applications and harsh environments
- Current rating 40 Amp continuous, 50 Amp audio with 50% duty cycle
- Uses precise "Quick Lock" system
- Mates with all currently available speakON products
- Weatherproof built-in gasket meets IP 54 protection class in mated condition
- 4 pole version has UL Recognized components, CSA listed
- 4 type range - also male cable connector and female receptacle on 4-pole version

Technical Information [hide](#)

Product	
Title	NLT4MP-BAG
Connection Type	speakON
Gender	male
Electrical	
Contact resistance	< 2 mΩ (after lifetime)
Dielectric strength	4 kVdc (peak)
Insulation resistance	> 10 GΩ
Rated current per contact	40 A rms continuous
Rated current per contact	50 A audiosignal, duty cycle 50 %
Rated voltage	250 V (Insulation)
Attention	speakON is NOT to be used as an AC mains or power supply connector!
Mechanical	
Lifetime	> 5000 mating cycles
Locking device	Quick Lock
Chassis shape	square G-size flange
Layout	four thru holes
Material	
Contact plating	4 μm Ag
Contacts	Spring copper
Insert	Polyamide (PA 6 30 % GR)
Home Products About us Contact Support	

Insert (ZnAl4Cu1) black chrome

Environmental

Flammability

UL 94 HB

Protection class

IP 54 (mated condition)

Solderability

Complies with IEC 68-2-20

Temperature range

-30 °C to +80 °C

Accessories

CAS-DUMMY



NDL



SCL



SCNLT

