


## 1485A Multi-Conductor - 300V Power-Limited Tray Cable



For more Information  
please call

1-800-Belden1



### General Description:

16 AWG pairs stranded (7x24) bare copper conductors, twisted pairs, overall Beldfoil shield (100% coverage), PVC insulation, PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Conductors	# Pairs	AWG	Stranding	Conductor Material
	8	16	7x24	BC - Bare Copper
1		22	7x30	BC - Bare Copper

Total Number of Conductors: 17

#### Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.432

#### Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire	Conductor Material
16	7x24		TC - Tinned Copper

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	1.3462

Outer Jacket Ripcord: Yes

#### Overall Cable

Overall Cabling Lay Length & Direction:

Length (mm)
222.249125

Overall Nominal Diameter: 16.078 mm

#### Pair

Pair Color Code Chart:

Number	Color
1	Black & White and Numbered 1
2	Black & White and Numbered 2
3	Black & White and Numbered 3
4	Black & White and Numbered 4
5	Black & White and Numbered 5
6	Black & White and Numbered 6
7	Black & White and Numbered 7
8	Black & White and Numbered 8
Communication Wire	Orange

**Pair Lay Length & Direction:**

Lay Length (mm)
76.200
76.200

### Mechanical Characteristics (Overall)

<b>Operating Temperature Range:</b>	-30°C To +105°C
<b>Bulk Cable Weight:</b>	360.144 Kg/Km
<b>Max. Recommended Pulling Tension:</b>	2700.057 N
<b>Min. Bend Radius/Minor Axis:</b>	158.750 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

<b>NEC/(UL) Specification:</b>	CMG, ITC-ER, PLTC-ER
<b>CEC/C(UL) Specification:</b>	CMG
<b>AWM Specification:</b>	UL Style 2464 (300 V 105°C)
<b>EU Directive 2011/65/EU (ROHS II):</b>	Yes
<b>EU CE Mark:</b>	Yes
<b>EU Directive 2000/53/EC (ELV):</b>	Yes
<b>EU Directive 2002/95/EC (RoHS):</b>	Yes
<b>EU RoHS Compliance Date (mm/dd/yyyy):</b>	04/01/2005
<b>EU Directive 2002/96/EC (WEEE):</b>	Yes
<b>EU Directive 2003/11/EC (BFR):</b>	Yes
<b>CA Prop 65 (CJ for Wire &amp; Cable):</b>	Yes
<b>MII Order #39 (China RoHS):</b>	Yes

#### Flame Test

<b>UL Flame Test:</b>	UL1685 FT4 Loading
<b>CSA Flame Test:</b>	FT4
<b>IEEE Flame Test:</b>	1202

#### Suitability

<b>Suitability - Burial:</b>	Yes
<b>Sunlight Resistance:</b>	Yes

#### Plenum/Non-Plenum

<b>Plenum (Y/N):</b>	No
----------------------	----

### Surface Printing (Overall)

<b>Surface Printing:</b>	BELDEN 1485A E34972 8PR16 1C22 SHIELDED (UL) CMG 105C OR PLTC-ER OR ITC-ER SUN RES DIR BUR OR AWM 2464 80C 300V OR C(UL) CMG----FT4 IEEE1202 (2 FT, 7 DIGIT SEQUENTIAL NUMBER) FEET
--------------------------	---

### Electrical Characteristics (Overall)

#### Nom. Conductor DC Resistance:

Description	DCR @ 20°C (Ohm/km)
16 AWG	12.0413
22 AWG	48.2307

#### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
10.1711

## 1485A Multi-Conductor - 300V Power-Limited Tray Cable

**Max. Operating Voltage - UL:**

<b>Voltage</b>
300 V RMS

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1485A 0107500	7,500 FT	2,040.000 LB	BLACK	C Z	8 PR #16 + 1 #22 PVC FS PVC

**Notes:**

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 3    Revision Date: 11-10-2015

© 2019 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).