


VIDEO CABLE HD-SDI



DIGITAL

HD-SDI

HALOGEN FREE

GAV 7510 HD FRNC-C

CONSTRUCTION DATA

Inner conductor	1,02 mm Ø (AWG 20) Bare Copper
Insulation	4.8 mm Ø Gas-injected foam
Shielding	Aluminum Foil % 100
Shielding	Tinned Copper Braiding % 95
Outer Jacket	HFFR Compound
Outer Diameter	7 mm Ø
Cable Weight	68 Kg/Km

ELECTRICAL DATA

DC resistance	< 22 Ω / km (Inner conductor) < 7 Ω / km (Shield)
Mutual capacitance	56 pF / m
Velocity of Propagation	80%
Characteristic Impedance	75 Ω ± 1
Screening factor	≥ 100 dB
Max. Operating Voltage	300 V Rms
Attenuation (db /100 Mt)	Return loss (dB)

Frequency (MHz)	Attenuation(db /100 Mt)	Frequency (MHz)	(dB)
1	0,9	50 – 300	≥ 26
10	2,2	300 – 3000	≥ 22
30	3,5	3000 – 3500	≥ 18
100	6,3	3500 – 5000	≥ 15
270	10,7		
540	15,3		
720	17,8		
800	19,2		
1000	22,1		
1500	26		
2000	29,8		
2250	32,5		
3000	38,7		

FLAME RESISTANCE:

IEC Flammability:	IEC 60332-1-2 and IEC 60332-3-24
-------------------	----------------------------------

MECHANICAL DATA

Minimum bending radius	10 x D (D= outer diameter)
Temperature range	-30° C to +70° C

APPLICATION

Gabriel coaxial video cable meets all the requirements of the Broadcast installations for HDTV and SDI high-definition video in spite of its reduced diameter.

The inner conductor insulation is made of a special gas-injected dielectric HDPE which guarantees a very low capacitance value.

For analogue and digital video signals transmission.

These cable products have low smoke density, halogen free and they don't emit poisonous gases.

ISO9001
CERTIFIED



CE

MOBIL
STUDIO
INSTALLATION
STAGE
GABRIEL