

GAP 22 SMART 2x0,22 SnCu PVC

Construction

Conductor	Tinned stranded copper wire, 7x0,20 mm
Insulation	PE compound, $\varnothing=1,02 \pm 0,05$ mm
Core identification	Red, Black
Lay-Up	Cores twisted together with 7x0,20 mm tinned copper wire & wrapped with ALPET foil
Sheath	PVC soft compound
Sheath color	Black

Marking

GABREAL GAP 22 SMART 2x0.22mm² AUDIO PATCH CABLE PVC LOT CE 0001 m

Technical data

Capacitance (core-core)	92,0 pF/m
Capacitance (Core-screen)	180,0 pF/m
Inductance	0,75 mH/km
Temperature range	
Flexible	-5°C to +50°C
Fixed	-30°C to +70°C
Min. bending radius	10 x Cable diameter

Properties

Flame retardant acc. to IEC 60332-1

Technical and dimension table

No of cores and cross sectio	Outer dimension	Conductor resistance at 20 °C	Insulation resistance	Cable weight	Copper weight
N x 2 x mm ²	Nom. (mm)	Max. (Ω/km)	Nom. (MΩ x km)	Nom. (kg/km)	Nom. (kg/km)
2 x 0,22	3,10 ± 0,10	96,0	1000	17	6,0

*The values can have small deviations