

## GABREAL GAT 240 PRoFLEX TWINAX 2x4,0 PVC

### Construction

Conductor	Plain bare copper, stranding to class5 (EN 60228), 4,0 mm <sup>2</sup> (127/0,20)
Insulation	PVC, Ø4,20 ± 0,05 mm
Core identifications	Blue, Red
Primary lay-up	Conductors stranded together
Outer sheath	PVC compaund (Flex) (Pressure type)
Outer sheath color	Black

### Marking

GABREAL GAT 240 PRoFLEX 2x4,0 TWINAX PVC SPEAKER CABLE LOT CE 0001 m

### Technical data

Conductor DC resistance	max. 4,95 Ω/km
Working temperature	Fixed -30 °C to +70 °C
	Flexible -5 °C to +70 °C
Bending radius	Moved: 15 x D
	Fixed: 7,5 x D

### Properties

Flame retardant acc. to IEC 60332-1, 60332-3-24

### Technical and dimension table

No of cores and cross section	Copper weight	Cable weight	Cable Diameter	Insulation resistance
N x mm <sup>2</sup>	Nom. (kg/km)	Nom. (kg/km)	Nom. ± %10 (mm)	Min. (MΩ x km)
2 x 4,0	72,90	175	9,60	200