


Part Number: 8412

Microphone Cable, #20-2c, TC, O/A Braid, CM



Product Description

20 AWG stranded (26x34) high-conductivity TC conductors, EPDM rubber insulation, rayon braid, TC braid shield (85% coverage), cotton wrap, EPDM jacket.

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Conductors
20	26x34	High Conductivity TC - Tinned Copper	0.037 in	2
Total Number of Conductors:				2

Insulation:

Material	Nominal Wall Thickness
EPDM - Ethylene Propylene Diene Monomer Rubber	0.023 in

Color Chart 1:

Number	Color
1	White
2	Black

Outershield 1:

Type	Layer	Material	Coverage [%]
Braid	1	Cotton	
Braid	2	TC - Tinned Copper	85 %
Cotton Wrap in			

Outerjacket 1:

Material	Nominal Diameter	Separator Material
EPDM - Ethylene Propylene Diene Monomer Rubber	0.262 in	Rayon Braid

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR	Nominal Outer Shield DCR
10.6 Ohm/1000ft	4.5 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
33 pF/ft	58 pF/ft

Impedance:

Nominal Characteristic Impedance
67 Ohm

Current:

Max. Recommended Current [A]
4 Amps per conductor @ 25°C

Inductance:

Nominal Inductance
0.18 μ H/ft

Voltage:

Non-UL Voltage Rating
600V RMS

Use

Max Recommended Pulling Tension:	100 lbs
----------------------------------	---------

Temperature Range

Non-UL Temp Rating:	90°C °C
Operating Temp Range:	-50°C To +90°C °C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	2.75 in
-----------------------------	---------

Part Number

Plenum (Y/N):	No
---------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes

Product Variants

Part Number	Color	Put-Up Type	Length
8412	RED	Reel	1000 ft
8412	RED	Reel	305 m
8412 0021000	RED	Reel	1000 ft
8412	YELLOW	Reel	1000 ft
8412	YELLOW	Reel	305 m
8412 0041000	YELLOW	Reel	1000 ft
8412	BLUE, LIGHT	Reel	1000 ft
8412	BLUE, LIGHT	Reel	305 m
8412 0061000	BLUE, LIGHT	Reel	1000 ft
8412	BLACK	Reel	1000 ft
8412	BLACK	Reel	305 m
8412 0101000	BLACK	Reel	1000 ft
8412	BLACK	Reel	100 ft
8412	BLACK	Reel	30 m
8412 010100	BLACK	Reel	100 ft
8412	BLACK	Reel	250 ft
8412	BLACK	Reel	76 m
8412 010250	BLACK	Reel	250 ft
8412	BLACK	Reel	500 ft
8412	BLACK	Reel	152 m
8412 010500	BLACK	Reel	500 ft
8412	BLACK	Reel	1000 ft
8412	BLACK	Reel	305 m
8412	BLACK	UnReel	1000 ft
8412	BLACK	UnReel	305 m
8412 010U1000	BLACK	UnReel	1000 ft
8412	BLACK	UnReel	500 ft
8412	BLACK	UnReel	152 m
8412 010U500	BLACK	UnReel	500 ft
8412			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.