

Part Number: 8261

Analog Video, RG11, #18 Str TC, 95% BC Braid, PVC Jacket, CXC



Product Description

18 AWG stranded (7x26) .048" tinned copper conductor, polyethylene insulation, bare copper braid shield (95% coverage), PVC jacket.

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Coax
18	7x26	TC - Tinned Copper	0.048 in	1
Total Number of Conductors:			1	

Insulation:

Material	Nominal Diameter
PE - Polyethylene	0.285 in

Outershield 1:

Type	Material	Coverage [%]
Braid	BC - Bare Copper	95 %

Outerjacket 1:

Material	Nominal Diameter
PVCNC - Polyvinyl Chloride Non-Contaminating	0.405 in

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR	Nominal Outer Shield DCR
6.1 Ohm/1000ft	1.2 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Shield

20.5 pF/ft

Impedance:

Nominal Characteristic Impedance

75 Ohm

High Frequency (Nominal/Typical):

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.2 dB/100ft
10 MHz	0.7 dB/100ft
50 MHz	1.3 dB/100ft
100 MHz	2 dB/100ft
200 MHz	2.9 dB/100ft
400 MHz	4.2 dB/100ft
700 MHz	5.8 dB/100ft
900 MHz	6.8 dB/100ft
1000 MHz	7.1 dB/100ft

Delay:

Nominal Delay

Nominal Velocity of Propagation (VP) [%]

1.54 ns/ft

66 %

Inductance:

Nominal Inductance

0.114 μ H/ft

Voltage:

UL Voltage Rating

3700V RMS V

Use

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Max Recommended Pulling Tension:	143 lbs

Safety

UL Flammability:	VW-1
------------------	------

Temperature Range

Non-UL Temp Rating:	60°C °C
Operating Temp Range:	-40°C To +60°C °C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	4 in
-----------------------------	------

Part Number

Plenum (Y/N):	No
---------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	Yes
CEC/C(UL) Specification:	CXC
MII Order #39 (China RoHS):	Yes
RG Type:	11A/U
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No

Product Variants

Part Number	Color	Put-Up Type	Length
8261	BLACK	Reel	1000 ft
8261	BLACK	Reel	305 m
8261 0101000	BLACK	Reel	1000 ft
8261	BLACK	Reel	500 ft
8261	BLACK	Reel	152 m
8261 010500	BLACK	Reel	500 ft
8261			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.