



Part Number: 1302E.00500
CATSNAKE S/FTP Cat6a 24AWG/7 PVC

Product Description

CATSNAKE S/FTP Cat6a 24AWG/7 PVC

Technical Specifications

Suitable Applications:	Field deployable CAT6a patch horizontal and building backbone cable; CobraNET, eSnake, Ethersound, Digital audio over Ethernet; Support current and future Category 6A and 6 applications, such as: 10GBase - T(10 Gigabit Ethernet), 1000 Base - T (Gigabit Ethernet), 100 Base - T, 10 Base - T, FDDI, ATM; Compatible connectors Belden R301601 000S1 (T568A) and R301602 000S1 (T568B)
-------------------------------	--

Construction and Dimensions

Conductor:

Element	AWG	Stranding	Material	No. of Pairs
Individual shielded pair	24	Stranded	Bare copper	4
Total Number of Conductors:		8		
Total Number of Pairs:		4		
Min Elongation at Breakof Conductors:		10 %		

Insulation:

Element	Type	Material	Nominal Diameter
Individual shielded pair	Dielectric	Foamed Polyethylene	1.4 mm
Min Elongation at Breakof Insulation:		100 %	

Color Chart 1:

Number	Color
Pair 1	White & Blue
Pair 2	White & Orange
Pair 3	White & Green
Pair 4	White & Brown

Innershield:

Element	Type	Material	Coverage [%]
Individual shielded pair	Tape	Aluminum / Polyester	100 %
Aluminum facing outside			

Outershield 1:

Type	Material	Drainwire Material	Drainwire AWG	Min. Coverage [%]
Braid	Tinned copper	Tinned Copper	26	80 %

Outerjacket 1:

Material	Color	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
Matte rugged PVC	Black (RAL 9005)	7.9 mm	0.3 mm	0.7 mm

Min Elongation at Break of Jacket:	100 %
------------------------------------	-------

Min Tensile Strength of Jacket:	9 MPa
---------------------------------	-------

Electrical Characteristics

Conductor DCR:

Max. Conductor DCR	Max DCR Unbalanced Between Pairs [%]	Max. DCR Unbalanced Within Pair [%]
95 Ohm/km	4 %	2 Ohm

Capacitance:

Max. Capacitance Unbalance	Max. Mutual Capacitance
1,600 pF/m	56 pF/m

Min Insulation Resistance:	5000 MOhm*km
----------------------------	--------------

Impedance:

Nominal Characteristic Impedance
100 Ohm

Delay:

Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
25 ns/100m	77 %

High Freq:

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. PSANEXT	Min. PSAACRF	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	2.5 dB/100m	75.3 dB	72.3 dB	72.8 dB	69.8 dB	68 dB	65 dB	20 dB	67 dB	67 dB	40 dB	35 dB
4 MHz	4.6 dB/100m	66.3 dB	63.3 dB	61.7 dB	58.7 dB	56 dB	53 dB	23 dB	67 dB	66.2 dB	34 dB	23 dB
10 MHz	7.1 dB/100m	60.3 dB	57.3 dB	53.2 dB	50.2 dB	48 dB	45 dB	25 dB	67 dB	58.2 dB	30 dB	15 dB
16 MHz	9 dB/100m	57.2 dB	54.2 dB	48.3 dB	45.3 dB	43.9 dB	40.9 dB	25 dB	67 dB	54.1 dB	28 dB	10.9 dB
31.2 MHz	12.6 dB/100m	52.9 dB	49.9 dB	50.4 dB	47.3 dB	38.1 dB	35.1 dB	23.6 dB	67 dB	48.3 dB	25.1 dB	5.1 dB
62.5 MHz	18 dB/100m	48.4 dB	45.4 dB	30.4 dB	27.4 dB	32.1 dB	9.1 dB	21.5 dB	65.6 dB	42.3 dB	22 dB	
100 MHz	23 dB/100m	45.3 dB	42.3 dB	22.3 dB	19.3 dB	28 dB	25 dB	20.1 dB	62.5 dB	38.2 dB	20 dB	
125 MHz	25.8 dB/100m	43.8 dB	40.8 dB	18 dB	15 dB	26.1 dB	23.1 dB	19.4 dB	61 dB	36.3 dB	19 dB	
200 MHz	33.1 dB/100m	40.8 dB	37.8 dB	7.7 dB	4.7 dB	22 dB	19 dB	18 dB	58 dB	32.2 dB	17 dB	
250 MHz	37.3 dB/100m	39.3 dB	36.3 dB	2 dB	-1 dB	20 dB	17 dB	17.3 dB	56.5 dB	30.2 dB	16 dB	
300 MHz	41.1 dB/100m	38.1 dB	35.1 dB	-3 dB	-6 dB	18.5 dB	15.5 dB	17.3 dB	55.3 dB	28.7 dB		
500 MHz	54.3 dB/100m	34.8 dB	31.8 dB	-19.5 dB	-22.5 dB	14 dB	11 dB	17.3 dB	52 dB	24.2 dB		

Current:

Max. Recommended Current [A]

1.5 A

Voltage:

Voltage Rating [V]

72 V

Coupling Attenuation:

Element	Coupling Attenuation [dB]
	Type II V dB
Type II	
Coupling Attenuation Class:	Type II

Transfer Impedance:

Frequency [MHz]	Description	Transfer Impedance
1 Mhz	Grade 2	Max.50 mOhm/m
10 Mhz		Max.100 mOhm/m
30 Mhz		Max.200 mOhm/m
100 Mhz		Max.1000 mOhm/m

Use

Burning Load:	650 kJ/m
Max Recommended Pulling Tension:	75 N

Safety

ISO/IEC Flammability:	IEC 60332-1
-----------------------	-------------

Temperature Range

Installation Temp Range:	0 to +50 °C
Operating Temp Range:	-30 to +60 °C

Mechanical Characteristics

Min Bend Radius During Installation:	64 mm
Min Bend Radius During Operation:	32 mm

Standards

ISO/IEC Compliance:	ISO/IEC 11801 2nd edition (2002) and ISO/IEC 11801 Amendment 2 (2010)
ANSI Compliance:	ANSI/TIA/EIA 568-B.2-10 (2008)
CENELEC Compliance:	EN 50173-1 (2011)

History

Revision Number:	1
------------------	---

Product Variants

Part Number	Color	Put-Up Type	Length
1302E.00500			
1302E.00500	Black	Reel	152 m
1302E.00500	BLACK	Reel	3000 m
1302E.00500	Black	Reel	305 m
1302E.00500	Black	Reel	500 m
1302E.00500	Black	Reel	499 m
1302E.00500			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.