



Part Number: 7887A

Audio Snake Cable, #26-24pr, TC, Indiv. Shielded, CM

Product Description

Digital Audio Snake Cable, CM-Rated, 12-26 AWG tinned copper pairs, Datalene® insulation, individually shielded with Beldfoil® bonded to numbered/color-coded PVC jackets so both strip simultaneously, PVC jacket

Product Specifications

AG.Filter Attributes

Total Number of Conductors:	48
-----------------------------	----

Technical Specifications

APAC Standard

MII Order #39 (China RoHS):	Yes
-----------------------------	-----

Applicable Patents

Patent:	http://www.belden.com/p
---------	---

Bend Radius

Min Bend Radius/Minor Axis:	8.5 in
-----------------------------	--------

CCB-Sub-Part Number

Plenum (Y/N):	No
---------------	----

Contact Information

PHONE_NUM:	1-800-Belden1
------------	---------------

EU Directive

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01

General Electrical Parameters

Other Electrical Characteristic 1:	2/c 22 AWG equivalent DCR when connected to a 3-pin XLR
------------------------------------	---

North American Standard

CA Prop 65 (CJ for Wire & Cable):	Yes
-----------------------------------	-----

Use

Max Recommended Pulling Tension:	535 lbs
----------------------------------	---------

Impedance:

Nominal Characteristic Impedance

40 Ohm

Inductance:

Nominal Inductance

0.21 μ H/ft

Conductor DCR:

Nominal Conductor DCR	Nominal Inner Shield DCR
36 Ohm/1000ft	6.8 Ohm/1000ft

Color Chart 1:

Number	Color
1	Brown
2	Red
3	Orange
4	Yellow
5	Green
6	Blue
7	Purple
8	Gray

9	White
10	Black
11	Beige
12	Pink
1	Blue
2	White
3	Blue w/White Stripe
4	White w/Blue Stripe

Color Chart 2:

Number	Number
1	Brown
2	Red
3	Orange
4	Yellow
5	Green
6	Blue
7	Purple
8	Gray
9	White
10	Black
11	Beige
12	Pink

Delay:

Nominal Velocity of Propagation (VP) [%]
66 %

Voltage:

UL Voltage Rating
100V RMS V

Current:

Max. Recommended Current [A]

1 Amp per conductor @ 25°C

Innershield:

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
French Braid	BC - Bare Copper	95 %	TC - Tinned Copper	26	7x38 mm
		95 %			

Capacitance:

Nom. Capacitance Between Conductors in Quad	Nom. Capacitance Conductor to Other Conductor to Shield
57.4 pF/ft	39.2 pF/ft

Innerjacket:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.157 in

Insulation:

Material	Nominal Diameter
PE - Polyethylene	0.045 in

Outerjacket 1:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.828 in

Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Quads
26	19x38	BC - Bare Copper	0.02 in	12

Other Electrical Information:

Other Electrical Characteristic 1	2/c 22 AWG equivalent DCR when connected to a 3-pin XLR.
-----------------------------------	--

Outershield 1:

Drainwire Material	Drainwire AWG	Drainwire Construction n x D
TC - Tinned Copper	20	19x32 mm

Product Variants

Part Number	Color	Put-Up Type	Length
7887A	BLACK, MATTE	Reel	500 ft
7887A	MATTE BLACK	Reel	152 m
7887A B59500	BLACK, MATTE	Reel	500 ft
7887A			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.